

MIRAL KTX+

Semi-Synthetic-Motor Oil 10W/40

Description:

MIRAL KTX+ is an highly alloyed lightrun petrol and diesel engine oil of the latest generation, enabling by its additives, selection of base oils and its viscosity application an energy-saving operation of car diesel engines. To guarantee the lowest viscosity of the SAE 10W-range as well as simultaneously a low volatilization loss **MIRAL KTX+** lightrun engine contains synthetic components meeting the demands of high tech.

Characteristics

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- High oxidation and temperature stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

Effects

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results
- Reduced fuel consumption
- Optimal engine cleanliness
- Low oil consumption
- All-year operation

Usable for

| | |
|--------------------------------|----------------|
| SAE | 10W-40 |
| API | SL/CF/EC |
| ACEA | A3/B4 |
| We recommend this product for: | |
| MB | 229.1 |
| VW | 501.01, 505.00 |

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve-technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- CDI- HDI- and TDI-motors
- with CDi-technology
- Direct-injection
- with catalyst technology

Disposal:

- **MIRAL KTX+** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **MIRAL KTX+** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **MIRAL KTX+** when refilling.

MIRAL KTX+

| Article No. | Packaging unit | |
|--------------|----------------|--------|
| STL 1000 922 | Can | 1 L |
| STL 1000 923 | Can | 4 L |
| STL 1000 924 | Can | 5 L |
| STL 1000 925 | Can | 20 L |
| STL 1000 926 | Drum | 60 L |
| STL 1000 928 | Drum | 200 L |
| STL 1400 929 | PE-Container | 1000 L |

Typical characteristics:

| | | |
|----------------------------|---------|-------|
| Specific weight at 15°C | kg/m³ | 871 |
| Dynamic viscosity at -25°C | mPa.s | 6360 |
| Viscosity at 40°C | mm²/s | 98,80 |
| Viscosity at 100°C | mm²/s | 14,7 |
| Viscosity index | | 155 |
| Flash point COC | °C | 224 |
| Pourpoint | °C | -39 |
| Sulphate ashes | % | 1,29 |
| TBN | mgKOH/g | 10,0 |

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
07/2021