



FORTUNA FC2

Fuel-Economy Mid SAPS-HC-Synthetic-Motor Oil 5W30

Description:

FORTUNA FC2 is a further developed Fuel Economy (FE) HC- synthetic fuel-efficient engine oil with the viscosity SAE 5W-30.

The exceptional qualities of this high quality engine oil fulfil today's requirements and application conditions. It is optimally coordinated for prolonged oil change intervals.

FORTUNA FC2 is especially suitable for use in automobile petrol and diesel engines with subsequent exhaust treatment systems, which require engine oils with a low viscosity (ACEA C2) according to the manufacturer's instructions. The "low Ash" (Mid SAPS formula low ash content) protects the engine as well as the catalytic converter system.

Characteristics

- Extreme wear protection at all operating conditions
- Excellent viscosity-temperature behaviour
- Minimum loss through friction, more power for the engine
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability
- Maximum shear stability

Effects

- Reduces fuel consumption and exhaust emission
- Formulation for less fuel consumption and Low Ash
- Excellent cold start behaviour - fast supply of all lubrication points, especially of the hydraulic valve tappet
- Stable oil pressure
- Perfect and long lasting engine cleanliness
- Prevents motor from incrustation
- High performance reserves and high product stability, even at longest oil change intervals
- All-year operation

Usable for

SAE	5W-30
API	SN/CF/EC
ACEA	C2, A5/B5
ILSAC	GF-5
We recommend this product for:	
FIAT	9.55535-S1
HONDA	
HYUNDAI	
KIA	
MAZDA	
MITSUBISHI	
PSA	B71 2290
RENAULT	RN0700
SUBARU	
TOYOTA	

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with Valvetronic
- with catalyst technology
- Passenger car diesel engines
- with multivalve-technology
- with turbo charging
- with CDi-technology
- with diesel particle systems(DPF)
- with catalyst technology

Disposal:

- **FORTUNA FC2** is assigned to category 1 of used oils and thus is free for disposal.

Miscibility:

- **FORTUNA FC2** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **FORTUNA FC2** it is recommendable to use only **FORTUNA FC2** when refilling.

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
07/2020

Kuttenkeuler GmbH • Niederlassung Eschweiler • D-52249 Eschweiler • Fon +49 (0) 2403 / 793-0 • Fax +49 (0) 2403 / 793-18
email: info@kuttenkeuler.com • www.startol.de

FORTUNA FC2

Article No.	Packaging unit	
STL 1090 162	Can	1 L
STL 1090 164	Can	5 L
STL 1090 165	Can	20 L
STL 1090 166	Drum	60 L
STL 1090 168	Drum	200 L
STL 1490 169	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	851
Dynamic viscosity at -30°C	mPa.s	5390
Viscosity at 40°C	mm ² /s	64,1
Viscosity at 100°C	mm ² /s	11,0
Viscosity index		165
Flash point COC	°C	236
Pourpoint	°C	-42
Sulphate ashes	%	-
TBN	mgKOH/g	8,5

