



MIRAL TURBO 60

Fully Synthetic-Motor Oil 10W60

Description:

MIRAL TURBO 60 is a fully synthetic engine oil for highly loaded petrol and diesel car engines, particularly for uprated fuel injection and turbo engines.

MIRAL TURBO 60 is ideal for engines which are submitted to hardest conditions in motor sports.

With its broad viscosity SAE 10W-60 extremely high temperature stability can be assured.

MIRAL TURBO 60 is particularly suitable for use in motorcycles with 4-stroke engines to recommend both on-road and off-road.

Characteristics

- High wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- High cleaning capability
- High oxidation and temperature stability
- Prevents black sludge formation

Usable for

SAE	10W-60
API	SN/CF
ACEA	A3/B4
We recommend this product for:	
BMW	M Series
FIAT	9.55535-H3
MB	229.1
VW	501.00, 505.00

Effects

- Excellent cold starting behaviour
- Very good operating reliability
- Optimises motor performance
- Optimal engine cleanliness
- Low oil consumption
- High margin of performance and high product stability
- All-year operation

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- Suction diesel
- Turbo diesel
- CDI- and TDI motors
- Direct-injection
- with catalyst technology
- Motorcycles with 4-stroke engines

Disposal:

- **MIRAL TURBO 60** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **MIRAL TURBO 60** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **MIRAL TURBO 60** it is recommendable to use only **MIRAL TURBO 60** when refilling.

MIRAL TURBO 60

Article No.	Packaging unit	
STL 1000 982	Can	1 L
STL 1000 984	Can	5 L
STL 1000 985	Can	20 L
STL 1000 986	Drum	60 L
STL 1000 988	Drum	200 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	859
Dynamic viscosity at -25°C	mPa.s	5410
Viscosity at 40°C	mm ² /s	180
Viscosity at 100°C	mm ² /s	25,8
Viscosity index		180
Flash point COC	°C	226
Pourpoint	°C	-42
TBN	mgKOH/g	13,6

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
04/2020