



MIRAL KTX1

Lightrun-Motor Oil 10W40

Description:

MIRAL KTX1 SAE 10W/40 is a lightrun engine oil enabling by its modern additives, selection of grand oils and its viscosity application a smooth operation of passenger car gasoline and diesel engines.

Characteristics

- High wear protection
- Exceptional ageing and oxidation stability
- Extrem high temperature stability
- Very high lubrication stability
- Greatest possible engine cleanliness
- Low volatilization tendency

Usable for

SAE	10W-40
API	SL/CF/EC

Effects

- Suitable for extended oil change intervals
- Optimal operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Prevents black sludge formation
- Fuel efficiency by lightrun properties
- All-year operation

Utilization

- Four-stroke petrol engine
- with multivalve-technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- with turbo charging
- with catalyst technology

Disposal:

- **MIRAL KTX1** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **MIRAL KTX1** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **MIRAL KTX1** only.

MIRAL KTX1

Article No.	Packaging unit	
STL 1000 502	Can	1 L
STL 1000 503	Can	4 L
STL 1000 504	Can	5 L
STL 1000 505	Can	20 L
STL 1000 506	Drum	60 L
STL 1000 508	Drum	200 L
STL 1400 509	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	861
Dynamic viscosity at -25°C	mPa.s	5380
Viscosity at 40°C	mm ² /s	96,6
Viscosity at 100°C	mm ² /s	14,8
Viscosity index		158
Flash point COC	°C	228
Pourpoint	°C	-39
TBN	mgKOH/g	7,8

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
02/2018