

# MIRAL KTD

## Premium-Lightrun-Motor Oil 10W40

## **Description:**

MIRAL KTD is an highly alloyed lightrun diesel engine oil enabling by its additives, selection of grand oils and its viscosity application an energy-saving operation of car diesel engines. To guarantee the lowest viscosity of the SAE 10W-range as well as simultaneously a low volatilization loss MIRAL KTD lightrun engine contains full synthetic components meeeting the demands of high tech.

## Characteristics

- High wear protection
- Exceptional ageing and oxidation stability
- Excellent high temperature stability
- Very high lubrication stability
- Greatest possible engine cleanliness
- Low volatilization loss

### Usable for

SAE	10W-40			
API	CF/EC			
ACEA	B4			
We recommend this product for:				
MB	229.1			
PSA	B71 2296			
RENAULT	RN0700			
VW	505.00			

### **Effects**

- Suitable for extended oil change intervals
- · Optimal operating reliability
- Excellent cold starting properties rapid supply of all points of lubrication
- Prevents black sludge formation
- Fuel efficiency by lightrun properties
- All-year operation

## Utilization

- Passenger car diesel engines
- Suction diesel
- · Turbo diesel
- · CDI- HDI- and TDI-motors
- with CDi-technology
- Direct-injection
- with catalyst technology

## Disposal:

• MIRAL KTD is assigned to category 2 of used oils and thus is free for disposal.

#### Miscibility:

• MIRAL KTD engine oil is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take MIRAL KTD when refilling.

Packaging unit	
Can	1 L
Can	5 L
Can	20 L
Drum	60 L
Drum	200 L
	Can Can Can Drum

Typical characteristics:		
G : C : 14 4 150G	1 / 3	0.57
Specific weight at 15°C	kg/m³	856
Dynamic viscosity at -25°C	mPa.s	4240
Viscosity at 40°C	mm²/s	95,4
Viscosity at 100°C	mm²/s	15,0
Viscosity index		166
Flash point COC	°C	232
Pourpoint	°C	-39
Sulphate ashes	%	-
TBN	mgKOH/g	10,3

Data are subject to change. Attention: Service instructions should be observed!