

# LARGO HD (SAE 40)

## Super-Monograde-Motor Oil

### Description:

**LARGO HD (SAE 40)** is a monograde engine oil for the use of all brands of passenger car and truck diesel engines with and without turbocharging. An excellent additive packages provides high performance. Monograde engine oils are not suitable for all seasons, therefore they have to be changed accordingly, i.e. SAE 10W in winter and SAE 30 in summer (i.e. lawn-movers).

### Characteristics

- High lubrication film stability
- High oxydation- and thermo stability
- High engine cleanliness
- Excellent viscosity-temperature behaviour
- High safety potential, also at boundary lubrication conditions

### Usable for

SAE	40
API	SG/CF-4
MIL	L-2104 E
MIL	L-46152 E
We recommend this product for:	
ALLISON	C-4
CAT	TO-2
MAN	270
MB	228.0
MTU	Type 2

### Effects

- High operating reliability
- Prevents black sludge formation

### Utilization

- Four-stroke petrol engine
- with turbo charging
- with catalyst technology
- Commercial vehicle diesel engines
- with turbo charging
- with catalyst technology
- Stationary diesel engines
- Locomotive diesel engines
- Also in:
- Gearboxes
- Torque converters
- Hydraulic systems
- (if an appropriate motor oil is specified)

### Disposal:

- **LARGO HD (SAE 40)** is assigned to category 2 of used oils and thus is free for disposal.

### Miscibility:

- **LARGO HD (SAE 40)** engine oil is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **LARGO HD (SAE 40)** when refilling.

### LARGO HD (SAE 40)

Article No.	Packaging unit	
STL 1010 302	Can	1 L
STL 1010 304	Can	5 L
STL 1010 305	Can	20 L
STL 1010 306	Drum	60 L
STL 1010 308	Drum	200 L
STL 1410 309	PE-Container	1000 L

### Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	871
Viscosity at 100°C	mm <sup>2</sup> /s	13,8
Flash point COC	°C	222
Pourpoint	°C	-45
TBN	mgKOH/g	8,2

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/EINB/-  
02/2018