



# PRAGOS X14 (OTP PLUS SUPER TRUCK)

HC-Synthetic-Heavy Duty-Diesel-Motor Oil 10W40

## Description:

**PRAGOS X14 (OTP PLUS SUPER TRUCK)** is a HC synthetic multigrade lightrun diesel engine oil, especially for use in all types of diesel engines (without diesel particulate filter), in particular for all EURO 4 and EURO 5 engines.

**PRAGOS X14 (OTP PLUS SUPER TRUCK)** is especially created for the operation of highly strained diesel engines with and without turbocharging and effectively prevents "Bore Polishing" (reflector surface formation at the cylinder bore) well known at modern high performance diesel engines. It provides as UHPD-Oil maximum drain intervals (up to 100.00 km - according to the service instructions) and thus is especially recommendable for trucks of i.e. carriage transports.

**PRAGOS X14 (OTP PLUS SUPER TRUCK)** meets the European emission standards for diesel engines.

## Characteristics

- High wear protection
- Exceptional ageing and oxidation stability
- Reduces formation of ageing products at high temperatures
- Low volatilization tendency
- Excellent viscosity-temperature behaviour

## Effects

- Optimal operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Fuel efficiency by lightrun properties
- Minimum wear at highly strained engines
- Protection against reflector surface formation
- All-year operation
- Improved economy viability by extended inspections-intervals

## Usable for

SAE	10W-40
API	CI-4+ UHPD
ACEA	E4/E7
We recommend this product for:	
CATERPILLAR	ECF1.a, ECF-2
CUMMINS	CES 20076/77/78
DAF	HP-1/2
DETROIT DIESEL	DDC 93K215
DEUTZ	DQC IV-10
GLOBAL	DHD-1
IVECO	18-1804T3 E4
MACK	EO-M Plus
MAN	M 3377, M 3277
MB-Approval	228.5
MTU	Type 3
RENAULT VI	RXD, RLD-2
SCANIA	LDF-3
TATRA	TDS 40/16
TEDOM	258-4
VOITH	Retarder B
VOLVO	VDS 3
ZETOR	

## Utilization

- Passenger car diesel engines
- with turbo charging
- with catalyst technology
- Commercial vehicle diesel engines
- with turbo charging
- with catalyst technology

## Disposal:

- **PRAGOS X14 (OTP PLUS SUPER TRUCK)** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **PRAGOS X14 (OTP PLUS SUPER TRUCK)** is miscible with comparable lubrications. It is recommended to take only **PRAGOS X14 (OTP PLUS SUPER TRUCK)** when refilling

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/NKW/-  
07/2021

Kuttenkeuler GmbH • Niederlassung Eschweiler • D-52249 Eschweiler • Fon +49 (0) 2403 / 793-0 • Fax +49 (0) 2403 / 793-18  
email: info@kuttenkeuler.com • www.startol.de

**PRAGOS X14 (OTP PLUS SUPER TRUCK)**

Article No.	Packaging unit	
STL 1090 804	Can	5 L
STL 1090 805	Can	20 L
STL 1090 806	Drum	60 L
STL 1090 808	Drum	200 L
STL 1490 809	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m <sup>3</sup>	863
Dynamic viscosity at -25°C	mPa.s	6380
Viscosity at 40°C	mm <sup>2</sup> /s	94,0
Viscosity at 100°C	mm <sup>2</sup> /s	14,2
Viscosity index		156
Flash point COC	°C	224
Pourpoint	°C	-36
Sulphate ashes	%	-
TBN	mgKOH/g	12,7

