

PRAGOS M2 (OTP PLUS 2 TRUCK)

Heavy Duty-Multigrade-Motor Oil 15W40

Description:

PRAGOS M2 (OTP PLUS 2 TRUCK) is a very high categorized SHPD engine oil that meets the required emissions standards. PRAGOS M2 (OTP PLUS 2 TRUCK) is thus recommended for the Euro 2, Euro 3, Euro 4 and Euro 5 motor generation with EGR and/or SCR-technology (not for engines with particle filter).

PRAGOS M2 (OTP PLUS 2 TRUCK) is a universally usable all-year engine oil for all suction and charged diesel engines.

Usable for all, also under very extreme operation conditions. Also suitable for use in passenger car engines.

PRAGOS M2 (OTP PLUS 2 TRUCK) meets the requirements of extended oil changing intervals (please observe manufacturers' instructions).

Characteristics

- Exceptional high detergent effect which almost prevents residues in the combustion section
- Formation of cold sludge and residues in the engine and the oil pan are nearly prevented
- Optimal protection against corrosion, oxidation, wear and foaming
- Extremely high pressure susceptibility
- Very well cleaning capability
- Excellent ageing stability
- Excellent viscosity-temperature behaviour

Usable for

SAE	15W-40			
API	CI-4/SL + SHPD			
ACEA	E7			
We recommend this product for:				
CATERPILLAR	ECF-1, ECF-2			
CUMMINS	CES 20077/78			
DETROIT DIESEL	93K215			
DEUTZ	DQC III-10			
GLOBAL	DHD-1			
JASO	DH1			
MACK	EO-M Plus, EO-N			
MAN	M 3275			
MB-Approval	228.3			
MTU	Type 2			
RENAULT	RLD-1, RLD-2			
VOLVO	VDS-3			

Effects

- High operating reliability
- Very well suitable for difficult operating conditions
- Suitable for longest oil changing intervals
- Prevents black sludge formation
- Protection against reflector surface formation
- Improved economy viability by extended inspectionsintervals
- Minimum wear at highly strained engines
- High stable viscosity index
- All-year operation
- Reduction of kinds

Utilization

- Commercial vehicle diesel engines
- with turbo charging
- with catalyst technology
- with EGR technology
- with SCR technology
- Passenger car diesel engines
- with turbo charging
- with catalyst technology
- Four-stroke petrol engine
- with turbo charging
- with catalyst technology
- Arbeits- und Landmaschinen Dieselmotoren

Disposal:

PRAGOS M2 (OTP PLUS 2 TRUCK) is assigned to category 2 of used oils and thus is free for disposal.

PRAGOS M2 (OTP PLUS 2 TRUCK) is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill PRAGOS M2 (OTP PLUS 2 TRUCK) only.

Data are subject to change. Attention: Service instructions should be observed! STL/MO/NKW/-07/2021

Article No.	Packaging unit	
STL 1000 424	Can	5 L
STL 1000 425	Can	20 L
STL 1000 426	Drum	60 L
STL 1000 428	Drum	200 L
STL 1400 429	PE-Container	1000 L

Typical characteristics:		
Specific weight at 15°C	kg/m³	862
Dynamic viscosity at -20°C	mPa.s	3720
Viscosity at 40°C	mm²/s	94,9
Viscosity at 100°C	mm²/s	14,5
Viscosity index		158
Flash point COC	°C	232
Pourpoint	°C	-42
Sulphate ashes	%	-
TBN	mgKOH/g	11,3

