

# CALICON UN89

Universal-Multigrade-Gear Oil 80W90

## Description:

**CALICON UN89** universal multigrade-light-gear lubricant oil of viscosity class SAE 80W/90 is based on synthetic basic components. It differs from the classical hypoid GL 5 gear lubricant oils in its multifunctional character. It shows an exceptional oxidation and thermal endurance.

A special additive process enhances the change gear efficiency and reduces thereby the fuel consumption.

**CALICON UN89** multigrade-light-gear lubricant oil is a universal gear lubricant oil, purpose-designed for gear boxes and rear axles of passenger cars, light and heavy trucks where an API GL 4 or GL 5 gear lubricant oil is prescribed. It is excellent for universal use in workshops.

## Characteristics

- Very well wear protection
- Excellent oxidation and thermostability
- High shear stability
- Excellent viscosity-temperature behaviour
- High pressure susceptibility
- Excellent corrosion protection
- Prevents foaming
- Neutral towards metals and sealing materials

## Usable for

SAE	80W-90
API	GL-3/GL-4/GL-5
MIL	L-2105 D
We recommend this product for:	
MAN	3343 Type M
MB	235.0, 236.6
SCANIA	STO 1:0
VOLVO	1273.10
ZF	TE-ML 01,05A,07A,08,12A,16B/C/D ,17B

## Effects

- Optimal operating properties
- Reduces wear and background noises
- Good flow flexibility at low temperatures
- Flowability up to -30°C
- All-year operation
- Life-time suitably
- Reducing of sorts

## Utilization

- Universal usability in the whole transmission path of the vehicle in accordance with the manufacturer's regulation
- Passenger car, light and heavy trucks

## Disposal:

- **CALICON UN89** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **CALICON UN89** gear oil of hypoid range is fully tolerated with comparable lubrications and can be mixed. However, it is recommended to take only **CALICON UN89** when refilling.

## CALICON UN89

Article No.	Packaging unit	
STL 1020 092	Can	1 L
STL 1020 095	Can	20 L
STL 1020 096	Drum	60 L
STL 1020 098	Drum	200 L
STL 1420 099	PE-Container	1000 L

## Typical characteristics:

Specific weight at 15°C	kg/m³	905
Viscosity at 40°C	mm²/s	176,2
Viscosity at 100°C	mm²/s	16,5
Viscosity index		98
Flash point COC	°C	212
Pourpoint	°C	-30

Data are subject to change.

Attention: Service instructions should be observed!

STL/GE/-  
07/2021