

DOLGAN DOT 4

High-performance Brake Fluid

Description:

DOLGAN DOT 4 is a high performance brake fluid developed for the requirements of modern passenger car brake-systems with disc or drum brakes.

Characteristics

- Wet boiling point $> 160^{\circ}C$
- Boiling point > 260°C

Usable for

| Brake fluid | DOT 4 | |
|-------------|---------------------------|--|
| Exceeds | DOT3 | |
| | (US Federal Standard 116) | |
| FMVSS | 116 | |
| SAE | J 1704 | |
| ISO | 4925 Class 4 | |

Effects

- More safety by reduced boiling point drop
- For all hydraulic brake systems
- Miscible with brake fluids of equal specification

Utilization

• car brake system according to DOT 3/DOT 4

Special Notes:

- Please store brake fluid only closed originally. Close tank of brake fluid airtightly straight after usage.
- Please unconditionally observe manufacturers information when refilling brake fluid.
- When refilling the hydraulic brake system absolute cleanliness is nececcary.
- This fluid can cause damages at the paintwork.

Disposal:

• Brake fluid must be gathered and disposed separately. It may not be mixed with used oil.

Miscibility:

• **DOLGAN DOT 4** is well-tolerated to comparable brake fluids. However, to guarantee complete efficiency it is recommended to use only **DOLGAN DOT 4** when refilling.

| DOLGAN DOT 4 | | |
|--------------|----------------|--------|
| Article No. | Packaging unit | |
| STL 1210 000 | Can | 250 ml |
| STL 1210 001 | Can | 500 ml |
| STL 1210 002 | Can | 1 L |
| STL 1210 004 | Can | 5 L |
| STL 1210 007 | Can (tin) | 5 L |
| STL 1210 005 | Can | 20 L |
| STL 1210 006 | Drum | 60 L |
| STL 1210 008 | Drum | 200 L |