



# BANTAX CHS 22

Multi-function mineral special hydraulic fluid colour: green

## Description:

**BANTAX CHS 22** is a special, mineral-based hydraulic fluid for use in specially marked containers for liquids, for hydraulic support of leveling, steering, & brake systems.

**BANTAX CHS 22** was developed for vehicle hydraulics use in a temperature range between -40°C and 100°C.

## Characteristics

- High viscosity index
- High pressure susceptibility
- Reliable wear protection
- Good oxidation stability
- Reliable protection against corrosion
- No foaming
- High ageing stability
- Low pour point

## Usable for

DIN	51524 T23
ISO	7308
We recommend this product for:	
MB	343.0

## Effects

- Good flow flexibility at low temperatures
- High performance level
- Low freezing point
- Engine oil for all seasons

## Utilization

- Power steering gear
- Rear axle steering
- Level control system
- Active damping and engine support
- Hydrostatic drive for cooling fans, radiators, generators
- Shock absorber
- Central lock
- Electro hydraulic control of convertible tops

## Special Notes:

- Achtung: Dieses Produkt ist nicht mischbar und verträglich mit Bremsflüssigkeit DOT 3, 4, 5 oder 5.1. Für das Hydropneumatiksystem von Citroen-Fahrzeugen ist das mineralische LHM-Fluid Plus zu verwenden.

## Disposal:

- **BANTAX CHS 22** is assigned to category 2 of used oils and thus is free for disposal.

## Miscibility:

- **BANTAX CHS 22** is fully compatible with comparable central hydraulic fluids and can be mixed trouble-free. However, it is recommended to refill only **BANTAX CHS 22**.

## BANTAX CHS 22

Article No.	Packaging unit	
STL 1220 042	Can	1 L

Data are subject to change.

Attention: Service instructions should be observed!

STL/SP/-  
04/2017