

JAGO SYN 4T

Premium-Fully Synthetic-Motorcycles-Motor Oil 5W40

Description:

JAGO SYN 4T is a high-performance premium full synthetic engine oil for 4-stroke motorbikes. For highest demands at racings and for every day. Absolute lubrication reliability even at extremst stress. Maximum of wear protection at extremely loaded lubrication film.

Also well suitable for oil bath clutches.

No slip, stick and / or rough shifting of clutch discs.

Characteristics

- · High wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- · Very high cleaning capability
- Prevents black sludge formation
- Low volatilization loss

Effects

- Very good operating reliability
- Excellent cold starting properties rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Optimal engine cleanliness
- Low oil consumption
- Suitable for use at racing, streets and grounds
- · Also for wet clutches

Usable for

| SAE | 5W-40 | | |
|--------------------------------|---------|--|--|
| API | SL | | |
| We recommend this product for: | | | |
| JASO | MA2, MA | | |

Utilization

• High-performance and normal 4-stroke motorbikes

Disposal:

• JAGO SYN 4T is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

• **JAGO SYN 4T** is fully compatible to custumary HD oils and can be mixed without any doubts. However, to take full advantage of **JAGO SYN 4T** it is recommendable to use only **JAGO SYN 4T** when refilling.

| JAGO SYN 4T | | |
|--------------|----------------|-------|
| Article No. | Packaging unit | |
| STL 1050 822 | Can | 1 L |
| STL 1050 824 | Can | 5 L |
| STL 1050 825 | Can | 20 L |
| STL 1050 826 | Drum | 60 L |
| STL 1050 828 | Drum | 200 L |
| | | |
| | | |

| Typical characteristics: | | | | | |
|----------------------------|---------|------|--|--|--|
| Specific weight at 15°C | kg/m³ | 845 | | | |
| Dynamic viscosity at -30°C | mPa.s | 4200 | | | |
| Viscosity at 40°C | mm²/s | 81,5 | | | |
| Viscosity at 100°C | mm²/s | 14,0 | | | |
| Viscosity index | | 167 | | | |
| Flash point COC | °C | 220 | | | |
| Pourpoint | °C | -45 | | | |
| Sulphate ashes | % | 0,94 | | | |
| TBN | mgKOH/g | 7,7 | | | |

Data are subject to change. Attention: Service instructions should be observed!