

FABIA FS5 1G2

Fully-Synthetic fuel saving smooth running engine oil SAE 5W-20

Description:

FABIA FS5 1G2 is a high performance motor oil which was especially developed for the most modern passenger cars petrol and diesel engines that are operated with low viscosity fuel- saving motor oils. This motor oil is suitable for all types of vehicles for which this viscosity level is prescribed. This viscosity level is recommended for many vehicles from Honda, Ford and other leading manufacturers.

Characteristics

- Extrem wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Considerable wear reduction on cylinder and camshaft
- High oxydation- and thermo stability
- Low volatilization loss
- Very high cleaning capability
- Stable oil film at all operating temperatures

Usable for

SAE	5W-20
API	SP (RC)
ILSAC	GF-6A
We recommend this product for:	
CHRYSLER	MS-6395
DAIHATSU	
FORD	WSS-M2C960-A
FORD	WSS-M2C945-B1
GM	Dexos 1 Gen 2
HONDA	
ISUZU	
KIA	
LEXUS	
MAZDA	
NISSAN	
SUBARU	
SUZUKI	
TOYOTA	

Effects

- Reduces fuel consumption at full and partial loading
- Reduces emissions of particles and CO₂, is good for the environment
- Excellent cold starting behaviour
- Very good operating reliability
- Optimal engine cleanliness
- Very low oil consumption
- High margin of performance and high product stability
- All-year operation

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with fuel injection
- with turbo charging
- with catalyst technology
- Hybrid vehicles
- Passenger car diesel engines
- with multivalve-technology
- with turbo charging
- with CDi-technology
- with diesel particle systems(DPF)
- with catalyst technology

Disposal:

- **FABIA FS5 1G2** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **FABIA FS5 1G2** is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **FABIA FS5 1G2**, however, the use of **FABIA FS5 1G2** is worth recommending.

FABIA FS5 1G2

Article No.	Packaging unit	
STL 1090 432	Can	1 L
STL 1090 434	Can	5 L
STL 1090 435	Can	20 L
STL 1090 436	Drum	60 L
STL 1090 438	Drum	200 L
STL 1490 439	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	852
Dynamic viscosity at -30°C	mPa.s	4750
Viscosity at 40°C	mm ² /s	47,5
Viscosity at 100°C	mm ² /s	8,5
Viscosity index		157
Flash point COC	°C	230
Pourpoint	°C	-45
TBN	mgKOH/g	7,4

