

# FORTUNA M-SPECIAL

Low SAPS-HC-Synthetic-Motor Oil 0W30

#### **Description:**

**FORTUNA M-SPECIAL** is a high-performance HC-Synthetic smooth-running multigrade engine oil of the latest generation. The exceptional properties of this high-performance engine oils meet the current requirements and operating conditions of the low-SAPS engine oils.

It is perfectly adapted to prolonged oil change intervals.

**FORTUNA M-SPECIAL** is a high-performance HC-Synthetic smooth-running multigrade engine oil, developed for pump-nozzle diesel engines without WIV-systems and light diesel engines from General Motors vehicles. Due to its special composition this engine oil is perfectly suitable to meet several new OEM requirements. These properties additionally enable the use in gasoline and diesel engines both in salon cars and in transport vehicles with and without turbocharger.

The "Low Ash" (Low SAPS) recipe protects engine and catalytic converter system.

#### Characteristics

- Extreme wear protection at all operating conditions
- Excellent viscosity-temperature behaviour
- Minimum loss through friction, more power for the engine
- Very high cleaning capability
- Low volatilization loss
- High oxidation and temperature stability
- Maximum shear stability

# Usable for

| SAE                                     | 0W-30                  |  |
|---|------------------------|--|
| API                                     | SN/CF                  |  |
| ACEA                                    | C2, C3                 |  |
| We recommend this                       | product for:           |  |
| BMW                                     | Longlife-04            |  |
| GM                                      | Dexos 2                |  |
| MB                                      | 229.31, 229.51         |  |
| RENAULT                                 | RN0700/0710            |  |
| VW                                      | 502.00, 505.00, 505.01 |  |
|   |                        |  |
|   |                        |  |
| l e e e e e e e e e e e e e e e e e e e |                        |  |

#### **Effects**

- Reduces fuel consumption and exhaust emission
- Formulation for less fuel consumption and Low Ash
- Excellent cold start behaviour fast supply of all lubrication points, especially of the hydraulic valve tappet
- Stable oil pressure
- Perfect and long lasting engine cleanliness
- Prevents motor from incrustation
- High performance reserves and high product stability, even at longest oil change intervals
- All-year operation

## Utilization

- High-performance car diesel engines
- with multivalve-technology
- with turbo charging
- Direct-injection
- pump-jet
- CDI- and TDI motors
- · with CDi-technology
- with diesel particle systems(DPF)
- · with catalyst technology
- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with Valvetronic
- with intercooling
- with turbo charging
- with catalyst technology

## Disposal:

FORTUNA M-SPECIAL is assigned to category 2 of used oils and thus is free for disposal.

#### Miscibility:

FORTUNA M-SPECIAL is fully compatible to custumary HD oils and can be mixed without any doubts. However, to
take full advantage of FORTUNA M-SPECIAL it is recommendable to use only FORTUNA M-SPECIAL when
refilling.

Data are subject to change.
Attention: Service instructions should be observed!

STL/MO/PKW/-

| FORTUNA M-SPECIAL |                |        |  |
|-------------------|----------------|--------|--|
| Article No.       | Packaging unit |        |  |
| STL 1090 332      | Can            | 1 L    |  |
| STL 1090 333      | Can            | 4 L    |  |
| STL 1090 334      | Can            | 5 L    |  |
| STL 1090 335      | Can            | 20 L   |  |
| STL 1090 336      | Drum           | 60 L   |  |
| STL 1090 338      | Drum           | 200 L  |  |
| STL 1490 339      | PE-Container   | 1000 L |  |
|                   |                |        |  |

| Typical characteristics:   |         |      |
|----------------------------|---------|------|
| Specific weight at 15°C    | kg/m³   | 843  |
| Dynamic viscosity at -30°C | mPa.s   | 5720 |
| Viscosity at 40°C          | mm²/s   | 68,8 |
| Viscosity at 100°C         | mm²/s   | 12,3 |
| Viscosity index            |         | 179  |
| Flash point COC            | °C      | -    |
| Pourpoint                  | °C      | -48  |
| Sulphate ashes             | %       | -    |
| TBN                        | mgKOH/g | 8,5  |

