



PALAS PS5+

Premium-HC-Synthetic-Motor Oil 5W40

Description:

PALAS PS5+ is a high-performance low-friction engine oil of the new generation, which allows a fuel-efficient operation of car petrol and diesel engines.

This particular engine oil designed for modern uprated fuel injection and turbo engines.

Selected high-quality base oils of synthesis technology, together with a selected additive combination lead to product quality, meet and exceed all the requirements of modern cars.

Characteristics

- High wear protection
- Excellent viscosity-temperature behaviour
- Minimal frictional loss
- Very high cleaning capability
- Prevents black sludge formation
- Low volatilization loss

Effects

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Fuel efficiency by lightrun properties
- Optimal engine cleanliness
- Low oil consumption
- Extended oil change intervals
- Optimal oil pressure
- All-year operation

Usable for

SAE	5W-40
API	SN/CF/EC
ACEA	A3/B4
We recommend this product for:	
BMW	Longlife-01
LAMBORGHINI	
MASERATI	
MB	229.5
MB	226.5
OPEL	GM-LL-B-025
PORSCHE	A40
PSA	B71 2296
RENAULT	RN0700/0710
VW	502.00, 505.00

Utilization

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- with turbo charging
- with CDi-technology
- with catalyst technology

Disposal:

- **PALAS PS5+** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **PALAS PS5+** is fully compatible to customary HD oils and can be mixed without any doubts. However, to take full advantage of **PALAS PS5+** it is recommendable to use only **PALAS PS5+** when refilling.

PALAS PS5+

Article No.	Packaging unit	
STL 1000 602	Can	1 L
STL 1000 603	Can	4 L
STL 1000 604	Can	5 L
STL 1000 605	Can	20 L
STL 1000 606	Drum	60 L
STL 1000 608	Drum	200 L
STL 1400 609	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	856
Dynamic viscosity at -30°C	mPa.s	6010
Viscosity at 40°C	mm ² /s	-
Viscosity at 100°C	mm ² /s	14,3
Viscosity index		176
Flash point COC	°C	-
Pourpoint	°C	-39
TBN	mgKOH/g	10,4

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
02/2018