



AVAR A25

Multigrade-Motor Oil 20W50

Description:

AVAR A25 is a multigrade engine oil for the use in petrol and diesel engines.

Characteristics

- Multigrade engine oil
- Excellent viscosity-temperature behaviour
- Selected additives guarantee a good engine lubrication
- High safety potential, also at boundary lubrication conditions

Usable for

SAE	20W-50
API	SF/CD

Effects

- All-year operation
- Good cold starting properties
- High operating reliability
- Prevents black sludge formation

Utilization

- Four-stroke petrol engine
- with turbo charging
- with catalyst technology
- diesel engines
- with turbo charging
- with catalyst technology

Disposal:

- AVAR A25 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- AVAR A25 is fully compatible to comparable lubrications and can be mixed without any doubts.

AVAR A25

Article No.	Packaging unit	
STL 1010 822	Can	1 L
STL 1010 824	Can	5 L
STL 1010 825	Can	20 L
STL 1010 826	Drum	60 L
STL 1010 828	Drum	200 L
STL 1410 829	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	857
Dynamic viscosity at -15°C	mPa.s	1930
Viscosity at 40°C	mm ² /s	137
Viscosity at 100°C	mm ² /s	20,4
Viscosity index		172
Flash point	°C	228
Pourpoint	°C	-39
Sulphate ashes	%	-
TBN	mgKOH/g	7,0

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
02/2018