



AVAR A15

Multigrade-Motor Oil 15W40

Description:

AVAR A15 is a multigrade engine oil for the use in petrol and diesel engines. The favourable SAE category 15W/40 provides an unproblematic operation at all seasons.

AVAR A15 is usable as all-seasons oil.

Characteristics

- Multigrade engine oil
- Excellent viscosity-temperature behaviour
- Selected additives guarantee a good engine lubrication
- High safety potential, also at boundary lubrication conditions

Usable for

SAE	15W-40
API	SF/CD

Effects

- All-year operation
- Good cold starting properties
- High operating reliability
- Prevents black sludge formation

Utilization

- Four-stroke petrol engine
- with turbo charging
- with catalyst technology
- diesel engines
- with turbo charging
- with catalyst technology

Disposal:

- AVAR A15 is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- AVAR A15 is fully compatible to comparable lubrications and can be mixed without any doubts.

AVAR A15

Article No.	Packaging unit	
STL 1000 102	Can	1 L
STL 1000 104	Can	5 L
STL 1000 105	Can	20 L
STL 1000 106	Drum	60 L
STL 1000 108	Drum	200 L
STL 1400 109	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	857
Dynamic viscosity at -20°C	mPa.s	2460
Viscosity at 40°C	mm ² /s	90,8
Viscosity at 100°C	mm ² /s	14,4
Viscosity index		165
Flash point COC	°C	226
Pourpoint	°C	-45
Sulphate ashes	%	-
TBN	mgKOH/g	6,5

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
02/2018

Kuttenkeuler GmbH • Niederlassung Eschweiler • D-52249 Eschweiler • Fon +49 (0) 2403 / 793-0 • Fax +49 (0) 2403 / 793-18
email: info@kuttenkeuler.com • www.startol.de