



JAGO MAR 2T

Motor Oil for all 2-Stroke Outboard-Motors

Description:

JAGO MAR 2T is specially designed for all 2-stroke outboard engines developed ashless two-stroke oil that meets NMMA TC-W3.

Characteristics

- Excellent protection against rust and corrosion
- Can easily be mixed with gasoline
- High wear protection
- Extraordinary lubrication
- High oxidation stability
- Ash-free formula

Usable for

NMMA (BIA)	TC-W3
------------	-------

Effects

- Optimal operating reliability
- Prevents against deposits - spark-plug bridge formation
- Environment-friendly - low smoke formation
- Selfmixing in tank
- Selfmixing and for separate lubrication

Utilization

- All 2-stroke petrol outboard engines, jet skis, Personal Watercraft
- Typical mixture ratio of 1:50 - 2% (ideally lead-free) (Follow manufacturer's recommendation)

Disposal:

- **JAGO MAR 2T** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **JAGO MAR 2T** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **JAGO MAR 2T** only.

JAGO MAR 2T

Article No.	Packaging unit	
STL 1050 122	Can	1 L
STL 1050 124	Can	5 L
STL 1050 125	Can	20 L
STL 1050 126	Drum	60 L
STL 1050 128	Drum	200 L
STL 1450 129	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	876
Viscosity at 40°C	mm ² /s	35,6
Viscosity at 100°C	mm ² /s	6,29
Viscosity index		126
Flash point PM	°C	107
Pourpoint	°C	-30
TBN	mgKOH/g	8,7
Colour		Brown

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/2T/-
07/2021