XANA 6STEP ATF

Special-High-Performance-Transmission-Fluid

Description:

XANA 6STEP ATF is a modern low-viscosity high-performance HC-synthetic automatic transmission fluid specially developed for the requirements of modern-step automatic transmission of high-performance vehicles from the Middle, Upper Class and SUV's.
The high coefficient of friction ensures a nearly slip-free transmission of high torques.

Characteristics

- Adapted friction coefficient for sporty gear changes
- Prevents annoying friction vibrations
- Outstanding friction characteristics
- Excellent low temperature switching behavior
- Extrem wear protection
- Highest oxidation and aging stability
- Minimal foaming
- Neutral towards sealing materials

Effects

- Lowered viscosity for improved fuel efficiency
- Optimal operating reliability at extreme conditions
- Best lubrication
- Protection against adhesions
- Keeps the gear clean
- Prolongs the life and performance of the gearbox
- Visco-stability under extreme conditions in the high temperature area

Usable for

Utilization

Kuttenkeuler GmbH • Niederlassung Eschweiler • D-52249 Eschweiler • Fon +49 (0) 2403 / 793-0 • Fax +49 (0) 2403 / 793-18
email: info@kuttenkeuler.com • www.startol.de

We recommend this product for:	
GENERAL-MOTORS-CORPORATION	Dexron VI
AISIN WARNER	AW-1, JWS 3324 , AW F8 FXX
ATF	Type 3.0/3.1
BENTLEY	P/N PY112995PA
BMW/MINI	P/N 83 22 0 142 516, P/N 83 22 0 397 114, P/N 83 22 2 163 514 (BMW 8072 B), ATF3+
CHRYSLER/DODGE/JEEP	P/N 05127382AA, P/N 68043742AA
FORD/LINCOLN/MERCURY	P/N XT-10-QLV (LV), P/N XT-6-QSP or -DSP (SP)
GM/GMC/OPEL/SATURN	AW1, P/N 88863400, 88863401
HONDA/ACURA	DW-1
HONDA	082000-9017 (ATF Type 3.1)
HYUNDAI/KIA	NWS-9638 T-5, P/N 040000C90SG, SP-IV / SPH-IV
JAGUAR/LANDROVER	Fluid 8432
JASO	M315, Class 1A
LAND ROVER	P/N TYK500050, LR0022460
MASERATI	P/N 231603
MAZDA	FW 6A EL, FW 6AX EL
MB	236.12, 236.14, 236.41
MERCON	LV
MITSUBISHI	ATF-J3, SP-IV, Dia-Queen ATF-PA,SP-N,SPH-IV,SP-IV-RR
NISSAN/INFINITY	Matic-S
PORSCHE	P/N 000 043 304 00
SAAB	P/N 93 165 147 - AW-1
SHELL	3353/134/M-1375.4/12108
TOYOTA/LEXUS/SCION	WS, Scion FZ
VW/AUDI	G 052 533, G 055 005 (-A, A2), G 055 540 (A2), G 060 162 (A1,A2,A6)
ZF	Lifeguardfluid 5/6

- Motor vehicle automatic transmission according service instructions
- Not suitable for use in DCT/DSG- or CVT-transmissions

Disposal:

- **XANA 6STEP ATF** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **XANA 6STEP ATF** is only miscible with comparable lubrications and well tolerated. However, to get full advantage of **XANA 6STEP ATF** it is recommendable to use **XANA 6STEP ATF** when refilling.

XANA 6STEP ATF

Article No.	**Packaging unit**	
STL 1030 592	Can	1 L
STL 1030 595	Can	20 L
STL 1030 596	Drum	60 L
STL 1030 598	Drum	200 L
STL 1430 599	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m³	841
Dynamic viscosity at -40°C	mPa.s	-
Viscosity at 40°C	mm²/s	27,1
Viscosity at 100°C	mm²/s	5,6
Viscosity index		157
Flash point COC	°C	226
Pourpoint	°C	-45
Colour		Red