



CADON LLV

Fully-Synthetic-Ultra-High-Performance Fuel Economy Motoroil 0W-20

Description:

CADON LLV is a fully synthetic ultra- high performance fuel economy engine oil for passenger cars' gasoline and diesel engines with and without turbo chargers in passenger cars and transporters, especially out of the Volkswagen group. **CADON LLV** was especially designed to reduce fuel consumption and exhaust emission. Additionally the CO² emission could be reduced significantly.

This engine oil is not backwards compatible with VW 504.00/ 507.00 or other VW specifications.

Characteristics

- Highest wear protection
- Excellent viscosity temperature behaviour
- Quick oil feed of critical lubricating points
- Significant wear reduction on the cylinder, camshaft, plain bearings and piston rings
- High oxidation and temperature stability
- Low volatilization loss
- Very high cleaning capability
- Particularly low emission combustion

Usable for

SAE	0W-20
API	SN Plus
ACEA	C5
We recommend this product for:	
FORD	WSS-M2C 956-A1
PORSCHE	C20
VW	508.00/509.00
VW	TL 52577

Effects

- Reduces fuel consumption at full and partial loading
- Excellent cold starting properties - rapid supply of all points of lubrication
- Reduction of CO² and exhaust emissions
- Optimal engine cleanliness
- High performance reserves and high product stability, even at longest oil change intervals
- All-year operation

Utilization

- New VW four-stroke petrol engines with WIV systems
- with multivalve technology
- with turbo charging
- with catalyst technology
- with extended oil change interval
- New VW passenger car diesel engines with WIV systems
- with pump and nozzle engines
- with diesel particle systems(DPF)
- with CDi-technology
- with turbo charging
- with multivalve-technology
- with catalyst technology
- This motor oil is not backward compatible.

Disposal:

- **CADON LLV** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **CADON LLV** is fully compatible with conventional HD oils and can be mixed if necessary. In orderable to fully utilise the advantages of **CADON LLV**, however, the use of **CADON LLV** is worth recommending.

CADON LLV

Article No.	Packaging unit	
STL 1090 402	Can	1 L
STL 1090 403	Can	4 L
STL 1090 404	Can	5 L
STL 1090 405	Can	20 L
STL 1090 406	Drum	60 L
STL 1090 408	Drum	200 L
STL 1490 409	PE-Container	1000 L

Typical characteristics:

Specific weight at 15°C	kg/m ³	836
Dynamic viscosity at -35°C(CCS)	mPa.s	3980
Viscosity at 100°C	mm ² /s	8,1
Flash point COC	°C	234
Pourpoint	°C	-54
TBN	mgKOH/g	8,0

Data are subject to change.

Attention: Service instructions should be observed!

STL/MO/PKW/-
01/2024

Kuttenkeuler GmbH • Niederlassung Eschweiler • D-52249 Eschweiler • Fon +49 (0) 2403 / 793-0 • Fax +49 (0) 2403 / 793-18
email: info@kuttenkeuler.com • www.startol.de