



# XANA 17LV ATF

## Special-High-Performance-HC-Synthetic-Automatic-Transmission-Fluid

### Description:

XANA 17LV ATF is a high quality and modern high- performance HC- synthetic automatic transmission oil with a reduced viscosity, especially developed for use in the latest Mercedes- Benz 9-shift automatic transmissions (9G- Tronic/ NAG 3 model 725 011).

This ATF gear oil is not backwards compatible. So it is not suitable for older gear boxes.

Please follow manufacturer´s instructions!

### Characteristics

- Extrem wear protection
- Adapted friction characteristics
- Excellent low-temperature-switching behavior
- Anti-flatter stability, resistance to friction
- Highest oxidation stability
- Minimal foaming
- Neutral towards metals and sealing materials
- Excellent cooling performance

### Usable for

We recommend this product for:	
MB	236.16, 236.17
MB	236.41
AISIN	AW F8FXX
DSIH	6p805 (Geely, Ssangyong, Mahindra,6sp)
HYUNDAI	NWS-9638
HYUNDAI/KIA	SP-IV, SPH-IV, SP-IV RR
JASO	1-A-LV
MITSUBISHI	ATF-J3, ATF-PA
MOPAR	68218925AA
NISSAN	MATIC S, MATIC W
SAAB	93 165 147
VOLVO	6 speed MY 2011-2013 (P/N 31256774, 31256675)
VW	G 052 540, G 055 005, G 055 162
ZF	6 Speed (S671 090 255)
ZF	TE-ML 13

### Disposal:

- XANA 17LV ATF is assigned to category 2 of used oils and thus is free for disposal.

### Miscibility:

- XANA 17LV ATF is only miscible with comparable lubrications and well tolerated. However, to get full advantage of XANA 17LV ATF it is recommendable to use XANA 17LV ATF when refilling.

### Effects

- Optimal operating reliability at extreme conditions
- Best lubrication
- Protection against adhesions
- Keeps the gearbox clean
- Prolongs the life and performance of the gearbox
- Visco-stability under extreme conditions in the high temperature area
- Maximum fuel savings due to reduced viscosity

### Utilization

- Motor vehicle automatic transmission according service instructions
- Not suitable for use in DCT/DSG- or CVT-transmissions

Data are subject to change.

Attention: Service instructions should be observed!

STL/GE/AU/-  
08/2021

**XANA 17LV ATF**

<b>Article No.</b>	<b>Packaging unit</b>	
STL 1030 572	Can	1 L
STL 1030 575	Can	20 L
STL 1030 576	Drum	60 L
STL 1030 578	Drum	200 L
STL 1430 579	PE-Container	1000 L

**Typical characteristics:**

Specific weight at 15°C	kg/m <sup>3</sup>	850
Viscosity at 40°C	mm <sup>2</sup> /s	30,4
Viscosity at 100°C	mm <sup>2</sup> /s	6,2
Viscosity index		162
Flash point COC	°C	> 190
Pourpoint	°C	-45
Colour		Yellow-Brown

