



FREECOOL RND ready for use -30°C

Ready-for-use Permanent Coolant (free of silicates) Colour: yellow/green

Description:

FREECOOL RND ready for use -30°C is a ready-to-use, ethylene glycol-based permanent coolant for summer and winter use with antifreeze and anticorrosion properties (all-season use).

With **FREECOOL RND ready for use -30°C**, the silicate-free carboxylate technology enables long-term protection for all applied materials on the engine, especially for aluminum and iron alloys.

FREECOOL RND ready for use -30°C offers a long- lasting corrosion protection by the use of optimized organic corrosion inhibitors.

FREECOOL RND ready for use -30°C is free of nitrite, amine, phosphate and silicate.

Characteristics:

- Longer and outstanding corrosion protection
- Improved heat transfer
- Decreased right to compensation regarding repairs at the cooling system
- Environmentally friendly by the use of carboxylates
- Avoidance of foaming
- Compatibility with hose and sealing materials
- Compatibility with varnishes
- Improved heat pump performance

Usage:

FREECOOL RND ready for use -30°C can be used without restrictions in engines out of cast iron, aluminum and/ or a combination out of both metals in cooling systems made out of aluminum or copper alloys.

FREECOOL RND ready for use -30°C is particularly recommended for high- tech engines that require special aluminum protection at higher temperatures.

Usable for:

| We recommend this product for: | |
|--------------------------------|---------------|
| DACIA | 41-01-001/--T |
| MB | 325.7 |
| RENAULT | 41-01-001/--T |

Miscibility:

- **FREECOOL RND ready for use -30°C** is miscible with several coolants based on ethylene glycol. For an optimal corrosion protection and to prevent sludge formation the unmixed use of **FREECOOL RND ready for use -30°C** is recommended.

FREECOOL RND ready for use -30°C

| Article No. | Packaging unit | |
|--------------|----------------|---------|
| STL 3100 343 | Can | 1500 ml |
| STL 3100 344 | Can | 5 L |
| STL 3100 345 | Can | 20 L |
| STL 3100 346 | Drum | 60 L |
| STL 3100 348 | Drum | 200 L |
| STL 3100 349 | PE-Container | 1000 L |

Data are subject to change.

Attention: Service instructions should be observed!

STL/WINTER/
07/2021